

5-1000MHz TRUNK DISTRIBUTION AMPLIFIERS

- RFI shielded aluminum die-cast housing for all weather outdoor strand-hang or pedestal mounts.
- Protection against surge and atmospheric by surge arresters at input and output ports.
- Test ports provided at input and output.
- Built-in tap-off output with appropriate values.
- 10 amp current passing.



MODEL#	TAMP-22	TAMP26	TAMP-30
Gain (±dB)	22	26	30
Flatness (dB)	±1	±1	±1
Return Loss	>12	>12	>12
Noise	7.5	7.5	7.5
CTB (dB)	72	72	72
CSO (dB)	94	98	98
Channel Capacity	77	77	77
Out Slope (dB)	3	3	3
AGC/ASC	±3/±0.3	±3/±0.3	±3/±0.3
Cross Modulation	83	81	73
Hum Modulation	>66	>66	>66



Model	MHz	Gain	Output DBuV	Amplifier Modules	Controllable Gain Slope	Automatic Control**	Return Path Band Gain MHz dB	Power Type
T4732M	70-750	26,30,34	98,102,106	Power Doubles	0-20dB 1dB/Step	AGS,ASC	5-50 0/16	60V
T4733L	47-550	22,26,30	94,98,102	Power Doubles		AGS,ASC		Switching
T4733M	47-750	26,30,34	98,102,106	Power Doubles		AGS,ASC		
T4735L	47-550	30	120	Push-pull	6-20dB	ATC	60V sw or R-Core Trans 220V r-core	
T4735M	47-750	36						
T4736L	47-550	30/36			adj			