

PLC Plug-in Cassette Splitter Specification

Application:

1x4/1x8/1x16/1x32/1x64 PLC Splitter Box package 130x100x25mm, PLC Splitter Cable Length 0.35+0.05/-0m, 5pcs or 9pcs Blue SC/UPC or SC/APC Adapter.

Feature:

- The loss is insensitive to the wavelength of light and can meet the transmission needs of different wavelengths.
- Uniform spectral distribution can evenly distribute signals to users.
- Compact structure, small size, can be directly installed in various existing junction boxes without leaving a large installation space.
- There are many branching channels for a single device, which can reach more than 32 channels.
- Multi channel has low cost, and the more branches there are, the more obvious the cost advantage.



Technical characteristics for splitter:

Model No.	MCR-Cassette SA 1x4/8			
Parameters	Symbol	Specifications		Unit
Channel Number	Ch	1X4	1X8	
Return Loss	RL	≥ 55		dB
Directivity ²	Dir	≥ 55		dB
Input Optic Power	P	100		mW
Fiber Type		G652D/ G657A fiber		
Connector Type		SC/UPC/APC		
Operation Temperature	Top	130 × 100 × 25		°C

Note: All insertion loss values not include the loss of the connector.

.....

If you need more information, please contact us!